

No one does it like you

Canon

THE COMPACT DEVICE THAT DELIVERS ON QUALITY AND EFFICIENCY

The imageRUNNER ADVANCE C475i III is ideally suited to small businesses that need access to a fast, reliable and easy-to-maintain printer.



imageRUNNER ADVANCE
C475i/C475iZ III
Multifunction A4 Laser Colour Printer

PERFORMANCE

Save time and resources, increasing productivity with efficient workflows and intuitive ease-of-use.

- Vivid and vibrant colour delivers a crisp, even finish.
- The advanced user interface takes users on a journey that is understandable and simplistic – helping them reach an end-point faster.
- Achieve maximum uptime with status notifications that help keep supplies replenished and intuitive maintenance videos for your high yield all-in-one toner cartridge replacement.

MOBILITY

Workers and contractors can achieve ultimate freedom and flexibility with Expanded Mobile OS Support

- Expanded mobile OS support adds flexibility and freedom to workplaces, enabling users to work 'on the go'.
- Canon PRINT Business (mobile app) makes managing workflows even easier and can be used with Apple and Android.

INTEGRATION

Seamlessly integrate with key line-of-business systems to fast track your digital transformation journey.

- Personalised workflows allow users to pick and choose what works best for them in terms of functionality.
- IT and office automation smoothly align thanks to a common source code for firmware and Canon's powerful Multifunctional Embedded Application Platform (MEAP).
- Supports integration with popular cloud services like Google Drive and Box*.

COST CONTROL

Improving operation efficiencies and better managing costs

- Forced job hold with ability to change print settings at device enhances control over projects.
- Blank page removal eliminates paper wastage and helps with document formatting.
- Track and assess print, copy, scan, and fax usage and allocate costs to departments or projects.

SUSTAINABILITY

Incorporating responsible design and efficient operation to help achieve environmental goals.

- Motion sensor/sleep recovery triggers are designed to ensure that the machine only operates when necessary so that power consumption is kept to a minimum.
- Bio-based plastics are used throughout the machine for an environmentally friendly approach to printing performance.
- EPEAT® rated and ENERGY STAR® qualified.

SECURITY

Safeguard data and ensure sensitive information remains secure.

- Standard HDD encryption is applied for tighter control over confidential documents and hardware data.
- Simplified management and security settings provide users and administrators with the ability to control security policies with ease from a centralised point.
- Verify that the device boot process, firmware and applications initialise without alteration at startup. McAfee Embedded Control™ utilises a whitelist to protect against malware and tampering of firmware and applications.

* Requires uniFLOW Online Express or uniFLOW Online subscription.

DEVICE SECURITY

The imageRUNNER ADVANCE C475i III Series feature the ability to help verify that the device boot process, firmware and applications initialise at startup, without any alterations or tampering by malicious third parties.

During operation, McAfee Embedded Control™ utilises a whitelist to protect against malware and tampering of firmware and applications.**



** These features are available on third generation imageRUNNER ADVANCE Gen III Series III models only. McAfee Embedded Control™ requires Unified Firmware Platform v3.9.

CONFIGURATION

imageRUNNER ADVANCE C475i III¹ (Standard Model)



Standard items

- UFR II
- PCL6
- Adobe PS 3
- Single Pass Document Feeder
- Direct Print Kit (XPS/PDF)
- HDD Data Encryption

imageRUNNER ADVANCE C475iZ III² (Finisher Model)



Cassette Feeding Unit-AS1

- Supports up to A4
- Media weight 60 to 163 gsm
- 1 x 500 sheets (80 gsm)
- Includes cabinet for storage



Cassette Feeding Unit-AT1

- Supports up to A4
- Media weight 60 to 163 gsm
- 1,500 sheet capacity
- Floor standing



Cassette Module-AJ1

- Supports up to A4
- Media weight 60 to 163 gsm
- 1 x 500 sheets (80 gsm)
- Desktop
- Can add up to two additional cassettes



1 Finisher cannot be added.

2 Finisher comes standard and cannot be removed.

imageRUNNER ADVANCE C475i/C475iZ III SPECIFICATIONS



Main Unit	
Machine Type	A4 Colour Laser Multifunctional
Core Functions	Print, Copy, Scan, Send, and Store
Processor	Canon Dual Custom Processor (Shared)
Control Panel	25.6 cm (10.1 inch) TFT LCD WSVGA Colour Touch Panel
Memory	Standard: 4.0 GB RAM
Hard Disk Drive	Standard: 320 GB (available disk space: 250 GB)
Interface Connection	Network Standard: 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n); Optional: NFC, Bluetooth Low Energy Others Standard: USB 2.0 (Host) x1, USB 3.0 (Host) x1, USB 2.0 (Device) x1; Optional: Copy Control Interface
Paper Supply Capacity (A4, 80 gsm)	Standard: 590 sheets Paper Cassette: 500-sheet cassette, 90-sheet Multi-purpose tray Maximum: 2,090 sheets (with Cassette Feeding Unit-AT1)
Paper Output Capacity (A4, 80 gsm)	Standard model (iR-ADV C475i III): 400 sheets Finisher model (iR-ADV C475iZ III): 900 sheets
Finishing Capabilities	Standard model: Collate, Group Finisher Model: Collate, Group, Offset, Staple
Supported Media Types	Multi-purpose tray: Thin, Plain, Recycled, Thick, Colour, Bond, Envelope Paper Cassette: Thin, Plain, Recycled, Thick, Colour, Label, Bond
Supported Media Sizes	Multi-purpose tray: Standard size: A4, A5, A5R, A6, B5, Envelopes (No.10 (COM10), Monarch, ISO-C5, DL) Custom size: 76.2 x 127.0 mm to 216 x 355.6 mm Paper Cassette: Standard size: A4, A5, A5R, A6, B5 Custom size: 101.6 x 148.0 mm to 216 x 355.6 mm
Supported Media Weights	Multi-purpose tray: 60 to 216 gsm Paper Cassette: 60 to 163 gsm Duplex: 60 to 163 gsm
Warm-up Time	From Power On: 10 seconds or less* * Time from device power-on, until copy ready (not print reservation) From Sleep Mode: 10 seconds or less Quick Startup Mode: 4 seconds or less* * Time from device power-on to when key operation can be performed on the touch panel display
Dimensions (W x D x H)	Standard model: 521 x 645 x 668 mm Finisher model: 521 x 645 x 864 mm When the optional Paper Feeding Unit is attached: Standard model: 642 x 668 x 1,124 mm Finisher model: 642 x 668 x 1,320 mm
Installation Space (W x D)	950 x 840 mm (with left cartridge door open + right door open + the cassette drawer open)
Weight (including Toner)	Standard model: Approx. 46 kg Finisher model: Approx. 55 kg
Print Specifications	
Print Speed* (ppm; BW and CL) * Simplex	iR-ADV C475i III/C475iZ III up to 47 (A4), up to 58 (A5), up to 39 (A5R), up to 49 (A6)
Print Resolution (dpi)	600 x 600, 1200 x 600
Page Description Languages	Standard: UFR II, PCL® 6, Genuine Adobe® PostScript® Level 3
Direct Print	Available from USB memory, Advanced Space, Remote UI and Web Access* Supported file types: TIFF, JPEG, PDF, EPS and XPS * Only PDF print from websites is supported
Printing from Mobile and Cloud	A range of software and MEAP-based solutions are available to provide printing from mobile devices or internet-connected devices and cloud-based services depending on your requirements. Please contact your sales representative for further information.
Fonts	PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T* (Japanese, Korean, Simplified and Traditional Chinese), Barcode fonts*2 PS fonts: 136 Roman *1 Requires optional PCL International Font Set-A1 *2 Requires optional Barcode Printing Kit-D1
Print Features	Suspend Job Timeout, Profile Settings, Secured Print, Encrypted Secure Print, Watermark, Header/Footer, Page Layout, Two-sided Printing, Collating, Booklet Printing, Grouping, Offsetting, Toner Reduction, Poster Printing, Forced Hold Printing
Operating System	UFR II: Windows® 7/8.1/10/Server 2008/2008 R2/2012/2012 R2/2016, MAC OS X (10.9 or later) PCL: Windows® 7/8.1/10/Server 2008/2008 R2/2012/2012 R2/Server 2016 PS: Windows® 7/8.1/10/Server 2008/2008 R2/2012/2012 R2/2016, MAC OS X (10.9 or later) PPD: MAC OS X (10.3.9 or later), Windows® 7/8.1/10
Copy Specifications	
Copy Speed* (ppm; BW and CL) * Simplex	iR-ADV C475i III/C475iZ III up to 47 (A4), up to 58 (A5), up to 39 (A5R), up to 49 (A6)
First Copy Out Time (A4; BW/CL)	Approx. 5.1/5.8 seconds or less
Copy Resolution (dpi)	600 x 600
Multiple Copies	Up to 9,999 copies
Copy Density	Automatic or Manual (9 Levels)
Magnification	Variable zoom: 25% to 400% (1% Increments) Preset reduction/enlargement: 25%, 50%, 70%, 100% (1:1), 141%, 200%, 400%
Copy Features	Preset R/E Ratios by Area, Two-sided, Density Adjustment, Original Type Selection, Interrupt Mode, Two-sided Original, Job Build, N on 1, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Copy ID Card, Skip Blank Pages, Color Mode, Reserved Copy, Copy Sample

Scan Specifications	
Type	Standard: Single-pass Duplexing Automatic Document Feeder* (Two-sided to Two-sided (Automatic with DADF)) * Detect Feeder Multi-Sheet Feed is supported.
Document Feeder Paper Capacity (80 gsm)	100 Sheets
Acceptable Originals and Weights	Platen: Sheet, Book, 3-Dimensional Objects Document Feeder Media Weight: 1-sided Scanning: 42 to 128 gsm (BW)*, 64 to 128 gsm (CL) 2-sided Scanning: 50 to 128 gsm (BW)*, 64 to 128 gsm (CL) * A6: 52 to 128 gsm (BW), 64 to 128 gsm (CL)
Supported Media Sizes	Platen: Max. Scanning Size: 216 x 355.6 mm Document Feeder media size: A4, A5, A6, B5, Custom size: 105.0 x 148 mm to 216 x 355.6 mm
Scan Speed (ipm; BW and CL, A4)	1-sided Scanning: 50 (300 x 300 dpi, send), 50 (300 x 600 dpi, copy), 30 (600 x 600 dpi, copy) 2-sided Scanning: 100 (300 x 300 dpi, send), 100 (300 x 600 dpi, copy), 50 (600 x 600 dpi, copy)
Scan Resolution (dpi)	600 x 600
Pull Scan Specifications	Colour Network ScanGear2. For both TWAIN and WIA Supported OS: Windows 7/8.1/10/Server 2008/Server 2008 R2/Server 2012/Server 2012 R2/Server 2016
Scan Method	Push Scan, Pull Scan, Scan to Box, Scan to Advanced Box, Scan to Network, Scan to USB Memory Key, Scan to Mobile device, Scan to Cloud (uniFLOW Online)
Send Specifications	
Destination	Standard: E-mail/Internet FAX (SMTP), SMB v3.0, FTP, WebDAV, Mail Box Optional: Super G3 FAX, IP Fax
Address Book	LDAP (2,000)/Local (1,600)/Speed dial (200)
Send Resolution (dpi)	Push: up to 600 x 600 Pull: up to 600 x 600
Communication Protocol	File: FTP (TCP/IP), SMB v3.0, WebDAV E-mail/I-Fax: SMTP, POP3
File Format	Standard: TIFF, JPEG, PDF (Compact, Searchable, Apply policy, Optimise for Web, PDF A/1-b, Encrypted, Device Signature), XPS (Compact, Searchable, Device Signature), Office Open XML (PowerPoint, Word) Optional: PDF (Trace and Smooth, User Signature), XPS (User Signature)
Universal Send Features	Original Type Selection, Two-sided Original, Book to Two Pages, Density Adjustment, Sharpness, Erase Frame, Job Build, Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-to, E-mail Priority, TX Report, Original Content Orientation, Skip Blank Pages
IP Fax Specifications	
Resolution (dpi)	400 x 400 (Ultra Fine), 200 x 400 (Super Fine), 200 x 200 (Fine), 200 x 100 (Normal)
Sending/Receiving Size	A4, A5*, A6* and B5* / A4, A5, B5 * Sent as A4
Store Specifications	
Mail Box (Number supported)	100 User Inboxes, 1 Memory RX Inbox, 50 Confidential Fax Inboxes, 30,000 Maximum Pages (2,000 jobs) Stored
Advanced Box	Communication Protocol: SMB or WebDAV Supported Client PC: Windows (Windows 8/10) Concurrent Connections (Max.): SMB: 64, WebDAV: 3
Advanced Box Available Disc Space	Approx. 16 GB (with Option: Max. 480 GB)
Advanced Box Feature	Authentication for Advanced Box Log-in, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support, Search, File Preview, Authentication Management, Open to Public, URI TX, Backup/Restore
Security Specifications	
Authentication and Access Control	Standard: User Authentication (Picture Login, Picture and PIN Login, Card Login, Username and Password Login, Function Level Login, Mobile Login), Department ID Authentication (Department ID and PIN Login, Function Level Login), uniFLOW Online Express (PIN Login, Picture Login, Picture and PIN Login, Card Login, Card and PIN Login, Username and Password Login, Department ID and PIN Login, Function Level Login), Access Management System (Access Control)
Device Security	Protecting HDD Data (HDD Data Encryption (FIPS140-2 Validated), HDD Data Overwrite Erase, HDD Lock), Standard HDD Initialise, Trusted Platform Module (TPM), Job Log Conceal Function, Protecting MFD Software Integrity, Checking MFD Software Integrity (Verify System at Startup, Runtime Intrusion Detection)
Network Security	IEEE802.1X Authentication, SNMP v3.0, Firewall Functionality (IP/MAC Address Filtering), Dual Network Support (Wired LAN/Wireless LAN, Wired LAN/Wired LAN), Disabling Unused Functions (Enabling/Disabling Protocols/Applications, Enabling/Disabling Remote UI, Enabling/Disabling USB Interface), Communication Line Separation (USB Port, Advanced Box, Scan and Send Virus Concerns for E-mail Reception)
Document Security	Print Security (Secure Print, Encrypted Secure Print, Forced Hold Printing, uniFLOW Secure Print*), Scan Security (Encrypted PDF, Device Signature PDF/XPS, User Signature PDF/XPS, BOX Security (Mail Box Password Protected, Advanced Box Access Control), Send Data Security (Setting for requesting password input per transmission, Restricted E-mail/File send functions, Allow/Restrict Sending from History, S/MIME Support), Scan Lock (QR code), Document Tracking (Secure Watermark) *1 Requires uniFLOW Online/uniFLOW
Environmental Specifications	
Operating Environment	Temperature: 10°C to 30°C Humidity: 20% to 80% RH (Relative Humidity)
Power Source	220–240 V, 50/60 Hz
Power Consumption	Maximum: Approx. 1,500 W Standby: Approx. 49.9 W Sleep Mode: Approx. 1.0 W
Standards	Blue Angel

Consumables

Toner Cartridges	Toner T04 BK/C/M/Y
Toner Yield	Toner T04 BK: 33,000 pages* Toner T04 C/M/Y: 27,500 pages* * Toner Cartridge yield in accordance with ISO/IEC 19798.

Software and Printer Management

Tracking and Reporting	Universal Login Manager (ULM): Manage your costs easily by using the embedded reporting capability to identify and control costs on a user-based level by device. uniFLOW Online Express: Combining with ULM you can gain further control and highlight expenditures per users/department and pinpoint where costs can be scaled down from a central cloud-based location.
Remote Management Tools	iW Management Console: Server-based software for centralised management of a fleet of devices (includes monitoring or consumables, status monitoring and alerts, distribution of address books, configuration settings, firmware and MEAP applications, meter capture and reporting, driver and resource management). eMaintenance: Compatible with eMaintenance services via embedded RDS (enables meter capture, automatic consumables management, remote diagnostics and reporting for service providers to offer efficient, fast and proactive maintenance). Content Delivery System: Allows the remote distribution of firmware, iR options and MEAP applications; Remote User Interface (RUI) web-based interface to each device that helps to provide remote device management and control.
Scanning Software	Network ScanGear: TWAIN-compliant scanner driver that enables computers on a network to use the pull scan functionality of the device.
Platform	MEAP (Multifunctional Embedded Application Platform): A powerful JAVA Embedded Platform for Canon devices which provides tight coupling between a range of software solutions and the device. MEAP Web: Web service alternative to MEAP that allows MFP applications to be developed and deployed via web services.

Paper Supply Options

Cassette Feeding Unit-AS1	Paper Capacity: 500 sheets (80 gsm) Paper Type: Paper Type: Thin, Plain, Recycled, Heavy, Colour, Labels, Bond Paper Size: A4, A5, A5R, A6, B5; Custom size: 101.6 x 148.0 mm to 216 x 355.6 mm Paper Weight: 60 to 163 gsm Power Source: From the Main Unit Dimensions (W x D x H): 642 x 657 x 456 mm (attached to the main unit) Weight: Approx. 19 kg
Cassette Feeding Unit-AT1	Paper Capacity: 500 sheets x 3 (80 gsm) Paper Type: Thin, Plain, Recycled, Heavy, Colour, Labels, Bond Paper Size: A4, A5, A5R, A6, B5; Custom size: 101.6 x 148.0 mm to 216 x 355.6 mm Paper Weight: 60 to 163 gsm Power Source: From the Main Unit Dimensions (W x D x H): 642 x 657 x 456 mm (attached to the main unit) Weight: Approx. 24 kg
Cassette Module-AJ1	Paper Capacity: 500 sheets (80 gsm) Paper Type: Thin, Plain, Recycled, Heavy, Colour, Labels, Bond Paper Size: A4, A5, A5R, A6, B5; Custom size: 101.6 x 148.0 mm to 216 x 355.6 mm Paper Weight: 60 to 163 gsm Power Source: From the Main Unit Dimensions (W x D x H): 521 x 474 x 130 mm (attached to the main unit) Weight: Approx. 7 kg

Output Features

Finisher Model (iR-ADV C475IZ III)	Number of Inner Trays: 2 Upper Tray Capacity*: A4, A5, B5, Custom size (148.0 x 210.0 mm to 216 x 355.6 mm): 400 sheets Lower Tray Capacity*: A4, A5, B5, Custom size (148.0 x 210.0 mm to 216 x 355.6 mm): 100 sheets * 80 gsm Paper Type: Thin, Plain, Recycled, Heavy, Colour, Bond Staple Paper Weight: 60 to 120 gsm (available with upper tray) Staple Position: Corner Staple Paper Size: A4; Custom size (210.0 x 279.4 mm to 216 x 355.6 mm) Staple Capacity: 30 sheets (60 to 90 gsm), 20 sheets (91 to 120 gsm)
------------------------------------	--

Hardware Accessories

Card Readers	MiCARDPLUS for ULM: A proximity card reader for card-based user authentication, supporting multiple card technologies (HID, HiTag, Casi Rusco, Indala and MiFare etc.). Integrates with Universal Login Manager and uniFLOW. Copy Card Reader-F1: Magnetic physical card access system. (Integrates with Department ID, not for use with uniFLOW). Copy Card Reader Attachment-B5: Attachment kit for Copy Card Reader-F1 only.
--------------	---

System and Controller Options

Print Accessories	PCL International Font Set-A1: Adds PCL support for Andalé Mono WT J/K/S/T (Japanese/Korean/Simplified Chinese/Traditional Chinese).
Send Options	Universal Send Trace and Smooth PDF Kit-A1: Enables the device to create and send Trace and Smooth PDF. Universal Send Digital User Signature Kit-C1: Ensures the authenticity of a PDF/XPS by identifying the user that sent the document through a visible and/or invisible digital signature.
Barcode Printing	Barcode Printing Kit-D1: Provides the ability to print 1D and 2D barcodes on output using jet caps technology.
System	Copy Control Interface Kit-A1: Allows connection (CCVI I/F) between third party copy control terminal and Canon's iR-ADV range for cost recovery use. Connection Kit-A1 for Bluetooth LE: Bluetooth chip is an option for enabling the communication between main unit and other devices using Bluetooth. NFC Kit-C1: NFC Control Panel is optional kit enabling the communication between main unit and other devices using NFC. For Flat panel.
Fax Accessories	Remote Fax Kit-A1: Enables the device to send and receive fax from another device connected with a fax board. IP Fax Expansion Kit-B1: Enables users to send and receive Fax documents via IP Fax network.

Other Options

Accessibility Accessories	ADF Access Handle-A1: Attaches to the document feeder, making access easier for seated users.
Staple Cartridge	Staple-P1: for Stapling (5,000 pcs x 2)

For information and services contact

Canon Australia Pty Ltd	1800 444 199	canon.com.au/business
Canon New Zealand Ltd	0800 222 666	canon.co.nz/business

POWERED BY  **uniFLOW**
online
express

*No one does it
like you*

Canon